

DATA SHEET

Premium Efficiency Motor: **PEWWE300-12-449T**

60 Hz

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 15-Feb-2023

Document ID:

Customer:

MOTOR INFORMATION

HP	300
RPM	1200
Phase	3
Frequency	60Hz
Voltage	460 V
Frame Size	449T
Enclosure	TEFC
Degree of Protection	IP55
Service Factor	1.15
Poles	6
Full Load Speed	1190
Insulation Class	F
Temp Rise	80°C
NEMA Code Letter	G
Duty Cycle	S1 / Continuous
Slip	0.83%
NEMA Design	B
Moment of Inertia	137 lb.ft.^2
Locked Rotor Time (Hot)	12 seconds
Sound Pressure Level	80 dB(A)
Number of Starts	2 Cold/ 1 Hot
Max Ambient Temperature	40°C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F1
Rotation	Bi-Directional
Area of Classification	Class I, Division 2, Groups A, B, C, D
Inverter Rating	10:1 CT / 20:1 VT PWM Type
Standard	NEMA MG-1
Approvals	CSA-US, CE

EFFICIENCY/POWER FACTOR

LOAD	EFF	P. F.
100%	95.8 %	0.83
75%	95.9 %	0.79
50%	95.6 %	0.7

TORQUE

FULL LOAD	LRT	BDT
1324 lb.ft.	190 %	250 %

AMPERAGE INFORMATION

	230V	460V
Full Load Amps	--A	353A
Locked Rotor Amps	--A	2200A
No Load Current	--A	141A
Usable at 208V	--A	

BEARING INFORMATION

DE Bearing	NU320 C3
ODE Bearing	6320 C3
Grease Type	SKF LGHP 2
DE Regreasing Interval	2000 Hours
ODE Regreasing Interval	2700 Hours


ADDITIONAL DATA

F2 Suitable	Yes
Shaft Material	4140 Carbon Steel
Connection Diagram	460 V - 6 Lead Δ
Approximate Weight	2957 lbs.

MOTOR DRAWING

Premium Efficiency Motor: **PEWWE300-12-449T**

WorldWide Electric Corporation
1 (800) 808-2131
Worldwideelectric.net



DIMENSION - INCHES

MOUNTING					A	B	C	D	G	J	P	O	T	AB
E	2F1	2F	H	BA										
9	20	25	0.81	7.5	21.339	30.472	56.945	11	1.575	3.346	23.554	22.969	4.213	19.171

SHAFT & KEY				
S	ES	R	N-W	U
0.875	6.91	2.88	8.5	3.375

TERMINAL BOX				
AA	XB	XC	XD	XF
2 X 3	4.7	11.813	11.339	21.087

PERFORMANCE CURVES

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Premium Efficiency Motor:

PEWWE300-12-449T


Document Generated: 15-Feb-2023

Document ID:


Customer:

Motor Type	PEWWE							
Output Rating (HP)	300			FL Speed	1190			
Full Load Torque	1324	lb.ft		LRT (%FLT)	190	460 volt FLA	353	A
Rotor Wk^2	137	lb-ft^2		BDT (%FLT)	250	230 volt FLA	--	A

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F. & CURRENT CURVE



NAMEPLATE / WIRING

Premium Efficiency Motor:

PEWWE300-12-449T

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 15-Feb-2023
Document ID:

Customer:

SAMPLE NAMEPLATE DATA

		NEMA Premium		3-PHASE INDUCTION MOTOR		259277 			
Model				Ser No.				Connection	
HP		S.F.		IP		Encl	6 4 5 1 2 3		
Frame		P.F.		Code		Type			
Voltage		Hz		Ins Cl		Rating	°C Amb Cont		
Amps		RPM		Design		Date			
Nom.Eff.	FL	% 3/4	%	V	10:1 CT	20:1 VT	PWM	VFD	1.0SF
Class I DIV. 2 Groups A B C D				Amb.40°C					
DE Brng				Grease type: LGHP 2					
ODE Brng				(compatible with polyrex)					
WorldWide Electric Corporation									

Model	PEWWE300-12-449T									
HP	300	S.F.	1.15	IP	IP55	Encl	TEFC			
Frame	449T	P.F.	0.83	Code	G	Type				
Voltage	460 V	Hz	60Hz	Ins Cl	F	Ambient	40°C			
Amps	353	RPM	1190	Design	B	DE Brng NU320 C3				
Nom.Eff.	FL	95.8%	3/4	95.9%	ODE Brng 6320 C3					
						Grease type: SKF LGHP 2				
50Hz	--	HP	--	--	A	-- rpm				