

DATA SHEET

Premium Efficiency Motor: **PEWWE5-18-184JM**

60 Hz

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 16-Feb-2023

Document ID:

Customer:

MOTOR INFORMATION

HP	5
RPM	1800
Phase	3
Frequency	60 Hz
Voltage	230/460 V
Frame Size	184JM
Enclosure	TEFC
Degree of Protection	IP55
Service Factor	1.25
Poles	4
Full Load Speed	1755
Insulation Class	F
Temp Rise	80°C
NEMA Code Letter	J
Duty Cycle	S1 / Continuous
Slip	2.50%
NEMA Design	B
Moment of Inertia	0.313 lb.ft. ²
Locked Rotor Time (Hot)	16 seconds
Sound Pressure Level	63 dB(A)
Number of Starts	2 Cold/1 Hot
Max Ambient Temperature	40°C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F1
Rotation	Bi-Directional
Area of Classification	Class I, Division 2, Groups A, B, C, D
Inverter Rating	10:1 CT / 20:1 VT PWM Type
Standard	NEMA MG-1
Approvals	CSA-US, CE

EFFICIENCY/POWER FACTOR

LOAD	EFF	P. F.
100%	89.5 %	0.83
75%	90.0 %	0.77
50%	89.2 %	0.66

TORQUE

FULL LOAD	LRT	BDT
15 lb.ft.	200 %	280 %

AMPERAGE INFORMATION

	230V	460V
Full Load Amps	12.6A	6.3A
Locked Rotor Amps	92A	46A
No Load Current	5.7A	2.85A
Usable at 208V	13.9A	

BEARING INFORMATION

DE Bearing	6307ZZ C3
ODE Bearing	6206ZZ C3
Grease Type	--
DE Regreasing Interval	- Hours
ODE Regreasing Interval	- Hours

ADDITIONAL DATA

F2 Suitable	No
Shaft Material	1045 Carbon Steel
Connection Diagram	230 / 460 V - 9 Lead Y
Approximate Weight	102 lbs.


MOTOR DRAWING

Premium Efficiency Motor: **PEWWE5-18-184JM**

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



DIMENSION - INCHES

MOUNTING					A	B	C	D	G	J	P	O	T	AB
E	2F1	2F	H	BAH										
3.75	4.5	5.5	0.41	3.37	9	7	18	4.5	0.6	2	9.7	9.5	1.42	8

SHAFT & KEY												
S	ES	R	AH	EQ	ET	EM	EL	EP	ER	EN	U	
0.188	1.65	0.768	4.25	0.625	2.875	1	1.25	1.378	4.27	3/8-16	0.874	

FLANGE				
AJ	AK	BB	BD	BF
5.875	4.5	0.156	6.6	3/8-16

TERMINAL BOX				
AA	XB	XC	XD	XF
1	2.2	5.1	4.6	6.13

PERFORMANCE CURVES

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Premium Efficiency Motor:

PEWWE5-18-184JM


Document Generated: 16-Feb-2023

Document ID:


Customer:

Motor Type	PEWWE				
Output Rating (HP)	5		FL Speed	1755	
Full Load Torque	15 lb.ft		LRT (%FLT)	200	460 volt FLA 6.3
Rotor Wk^2	0.313 lb-ft^2		BDT (%FLT)	280	230 volt FLA 12.6

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F. & CURRENT CURVE



NAMEPLATE / WIRING

Premium Efficiency Motor:

PEWWE5-18-184JM

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 16-Feb-2023
Document ID:

Customer:

SAMPLE NAMEPLATE DATA

		NEMA Premium		3-PHASE INDUCTION MOTOR		259277 		CE CC006A													
Model				Ser No.				Low Voltage													
HP		S.F.		IP		Encl		<table border="1"> <tr><td>4</td><td>5</td><td>6</td></tr> <tr><td>7</td><td>8</td><td>9</td></tr> <tr><td>1</td><td>2</td><td>3</td></tr> <tr><td>L1</td><td>L2</td><td>L3</td></tr> </table>		4	5	6	7	8	9	1	2	3	L1	L2	L3
4	5	6																			
7	8	9																			
1	2	3																			
L1	L2	L3																			
Frame		P.F.		Code		Type		High Voltage													
Voltage	230/460	Hz		Ins Cl		Rating	°C Amb Cont	<table border="1"> <tr><td>4</td><td>5</td><td>6</td></tr> <tr><td>7</td><td>8</td><td>9</td></tr> <tr><td>1</td><td>2</td><td>3</td></tr> <tr><td>L1</td><td>L2</td><td>L3</td></tr> </table>		4	5	6	7	8	9	1	2	3	L1	L2	L3
4	5	6																			
7	8	9																			
1	2	3																			
L1	L2	L3																			
Amps		RPM		Design		Date															
Nom.Eff.	FL	% 3/4	%	230/460V	10:1 CT	20:1 VT	PWM VFD	1.0SF													
				DE Brng																	
Class I DIV. 2 Groups A B C D				Amb.40°C		T3C(160°C)		ODE Brng													
Class I Zone 2 II C				Amb.55°C		T3A(180°C)		Grease type:													

Model	PEWWE5-18-184JM						
HP	5	S.F.	1.25	IP	IP55	Encl	TEFC
Frame	184JM	P.F.	0.83	Code	J	Type	
Voltage	230/460 V	Hz	60 Hz	Ins Cl	F	Ambient	40°C
Amps	12.6/6.3	RPM	1755	Design	B	DE Brng	6307ZZ C3
Nom.Eff.	FL	89.5%	3/4	90.0%		ODE Brng	6206ZZ C3
						Grease type:	--

50Hz 5 HP 200/400 V 15/7.49 A 1450 rpm