

DATA SHEET

Premium Efficiency Motor: **PEWWE10-9-284T**

60 Hz

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 15-Feb-2023

Document ID:

Customer:

MOTOR INFORMATION

HP	10
RPM	900
Phase	3
Frequency	60 Hz
Voltage	230/460 V
Frame Size	284T
Enclosure	TEFC
Degree of Protection	IP55
Service Factor	1.25
Poles	8
Full Load Speed	875
Insulation Class	F
Temp Rise	80°C
NEMA Code Letter	H
Duty Cycle	S1 / Continuous
Slip	2.78%
NEMA Design	B
Moment of Inertia	4.34 lb.ft.^2
Locked Rotor Time (Hot)	19 seconds
Sound Pressure Level	68 dB(A)
Number of Starts	2 Cold/ 1 Hot
Max Ambient Temperature	40°C
Max Elevation	1000 m.a.s.l (3300 f.a.s.l)
Mounting	F1
Rotation	Bi-Directional
Area of Classification	Class I, Division 2, Groups A, B, C, D
Inverter Rating	10:1 CT / 20:1 VT PWM Type
Standard	NEMA MG-1
Approvals	CSA-US, CE

EFFICIENCY/POWER FACTOR

LOAD	EFF	P. F.
100%	89.5 %	0.76
75%	89.9 %	0.70
50%	89.5 %	0.57

TORQUE

FULL LOAD	LRT	BDT
60 lb.ft.	170 %	250 %

AMPERAGE INFORMATION

	230V	460V
Full Load Amps	27.5A	13.8A
Locked Rotor Amps	162A	81A
No Load Current	14.6A	7.3A
Usable at 208V	30.4A	

BEARING INFORMATION

DE Bearing	6311 C3
ODE Bearing	6309 C3
Grease Type	SKF LGHP 2
DE Regreasing Interval	6800 Hours
ODE Regreasing Interval	8500 Hours

ADDITIONAL DATA

F2 Suitable	Yes
Shaft Material	1045 Carbon Steel
Connection Diagram	230 / 460 V - 12 Lead Δ
Approximate Weight	347 lbs.


MOTOR DRAWING

Premium Efficiency Motor: **PEWWE10-9-284T**

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



DIMENSION - INCHES

MOUNTING					A	B	C	D	G	J	P	O	T	AB
E	2F1	2F	H	BA										
5.5	--	9.5	0.53	4.75	13.74	12.244	26.362	7	0.866	2.756	13.976	14.283	2.047	11.239

SHAFT & KEY				
S	ES	R	N-W	U
0.5	3.28	1.591	4.62	1.875

TERMINAL BOX				
AA	XB	XC	XD	XF
1.5	3.645	7.381	6.299	9.5

PERFORMANCE CURVES

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Premium Efficiency Motor:

PEWWE10-9-284T


Document Generated: 15-Feb-2023

Document ID:


Customer:

Motor Type	PEWWE		FL Speed	875			
Output Rating (HP)	10		LRT (%FLT)	170	460 volt FLA	13.8	A
Full Load Torque	60	lb.ft	BDT (%FLT)	250	230 volt FLA	27.5	A
Rotor Wk^2	4.34	lb-ft^2					

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F. & CURRENT CURVE



NAMEPLATE / WIRING

Premium Efficiency Motor:

PEWWE10-9-284T

WorldWide Electric Corporation

1 (800) 808-2131

Worldwideelectric.net



Document Generated: 15-Feb-2023
Document ID:

Customer:

SAMPLE NAMEPLATE DATA

		NEMA Premium		3-PHASE INDUCTION MOTOR		259277 		CE CC006A	
Model					Ser No.				
HP		S.F.		IP		Encl			
Frame		P.F.		Code		Type			
Voltage	230/460	Hz		Ins Cl		Rating	°C Amb Cont		
Amps		RPM		Design		Date			
Nom.Eff.	FL	% 3/4	%	230/460V	10:1 CT 20:1 VT PWM VFD	1.0SF			
				DE Brng ODE Brng Grease type: LGHP 2 (compatible with polyrex)					
Class I DIV. 2 Groups A B C D		Amb.40°C		T3C(160°C)					
Class I Zone 2 IIC		Amb.55°C		T3A(180°C)					
50Hz	HP	V	A	rpm	S.F1.0				
WorldWide Electric Corporation									

Model **PEWWE10-9-284T**

HP **10** S.F. **1.25** IP **IP55** Encl **TEFC**

Frame **284T** P.F. **0.76** Code **H** Type

Voltage **230/460 V** Hz **60 Hz** Ins Cl **F** Ambient **40°C**

Amps **27.5/13.8** RPM **875** Design **B** DE Brng **6311 C3**

Nom.Eff. **FL 89.5% 3/4 89.9%** ODE Brng **6309 C3**

Grease type: **SKF LGHP 2**

50Hz 10 HP 200/400 V 33.2/16.6 A 725 rpm